

JavaScript is not activated: Please activate JavaScript in your Browser to use this website without restrictions.

This website may place cookies on your computer to help us improve your personal user experience. Please read our [privacy policy](#) to learn more about cookies. [Accept Cookies](#)

RICOH IMAGING Product ID: 101117 | Type: Unknown

English

- [Deutsch](#)
- [English](#)
- [Francais](#)
- [Italiano](#)

[txt_search_go](#)

- [Products](#)
 - [Lenses](#)
 - [Accessories](#)
 - [Work Assistance Camera System](#)
 - [Lens Selector](#)
 - [Product Search](#)
 - [Product Comparison](#)

[Close](#)
- [Support](#)
 - [Download](#)
 - [Technical Information](#)
 - [Newsletter](#)

[Close](#)
- [About us](#)
 - [About us](#)
 - [News](#)
 - [Contact](#)

[Close](#)

1. [Home](#)
2. >[Products](#)
3. >[Accessories](#)
4. >[Macro Focus Mount](#)

[Back](#) [Print page](#) [Save page as PDF](#)

Macro Focus Mount

The Macro Focus Mount is a special camera mount with a 2 mm tube extension. The C-Mount flange focal distance will then be extended by 2 mm to 19.526 mm which will in turn reduce the lenses minimum object

distance (M.O.D.).

In order to use our Macro Focus Mount, remove the standard C-mount on the lens and replace them with the appropriate mount above.

Please ensure you use the correct mount to lens as per the above chart. The FP-MU2M is designed for all the machine vision lenses except the FL-HC0614-2M and FL-CC7528-2M. In order to achieve even higher magnifications you can also use the close up adaptors and extension tubes.

1. [Macro Focus Mount](#)

[FP-MUVG](#)

2. [Macro Focus Mount](#)

[FP-MU2M](#)

[to top](#)

- [Imprint](#)
- [AGB](#)
- [Privacy Policy](#)
- [Warranty](#)

© 2024 Ricoh International B.V. - German Branch

Image not found or type unknown

